04-26-06

03:18pm

From-Ratner Prestia

610-407-0701

T-332 P.001/005 F-643



Suite 301, One Westlakes, Berwyn P.O. Box 980 Valley Forge, PA 19482-0980 610-407-0700 Phone: 610-407-0701 Fax:

Nemours Building 1007 Orange Street, Suite 1100 P.O. Box 1596 Wilmington, DE 19899 302-778-2500 Phone:

302-778-2600 Fax: www.ratnerprestia.com

Sulte 265 Commerce Corporate Center 5100 Tilghman Street Allentown, PA 18104 Phone: 610-530-8100

610-530-8200

## FAX FILING IN U.S. PATENT & TRADEMARK OFFICE

TIME: DATE: April 26, 2006

FAX NO.: 571-273-6982 TO: Examiner Deandra M. Hughes

ADMIN, ASST.: Kathleen Spina FROM: Lowell L. Carson, Reg. No. 48,548

ATTY. DOCKET NO .: TNT-114US APPLN, NO.: 10/644,570

TITLE OF APPLN.: PLACING A SEMICONDUCTOR LASER ELECTRICALLY IN SERIES WITH A SEMICONDUCTOR

OPTICAL AMPLIFIER

ART UNIT: 3663 FILING DATE: August 20, 2003

CONF. NO.: 6637 FIRST INVENTOR: Aaron Fisher

TITLE OF DOCUMENT (and List of Attachments): Claim set.

Total Number of Pages: 5 (including this form)

Examiner Aughes please find the claim set we discussed enclosed. Thanks, Le

## CONFIDENTIAL AND PRIVILEGED ATTORNEY/CLIENT INFORMATION

This facsimile transmission (and/or documents accompanying it) may contain attorney/client privileged communications and confidential business information that is intended for use only by the Individual or company to whom it is addressed. Disclosure, Interception, copying or any other use of this transmission by anyone other than any intended recipient is prohibited. If you receive this transmission by mistake, please notify the sender.

Please notify us immediately if you have not received the number of pages indicated above.

**TNT-114US** 

T-332 P.002/005 F-643

Appln. No.: 10/644,570

Amendments to the Claims: This listing of claims will replace all prior versions, and listings, of claims in the application

## **Listing of Claims:**



(Currently Amended) An amplified laser comprising:

a substrate,

a semiconductor optical amplifier (SOA), coupled to the substrate and including an amplifier anode electrode and an amplifier cathode electrode, and

a semiconductor laser, coupled to the substrate and including a semiconductor laser anode electrode and a semiconductor laser cathode electrode, and

an electro-absorption modulated laser (EML) package that encloses the semiconductor laser and the SOA, the EML package including:

a first electrical contact electrically coupled to at least one of the anode electrode of the SOA or the anode electrode of the semiconductor laser;

a second electrical contact electrically coupled to at least one of the cathode electrode of the SOA or the cathode electrode of the semiconductor laser; and

an optical output port configured to provide an output amplified optical signal:

wherein;

the semiconductor laser and the SOA are configured on the substrate so that the laser is optically coupled to the SOA; and

at least one of the semiconductor laser anode electrode or semiconductor laser cathode electrode is electrically coupled to at least one of the amplifier anode

Appln. No.: 10/644,570

**TNT-114US** 

electrode or amplifier cathode electrode such that the semiconductor laser and the SOA are electrically connected in series.

- (Canceled)
- (Previously Amended) An amplified laser comprising:

a substrate;

a semiconductor optical amplifier (SOA), coupled to the substrate and including an amplifier anode electrode and an amplifier cathode electrode;

a semiconductor laser, coupled to the substrate and including a semiconductor laser anode electrode and a semiconductor laser cathode electrode;

an electro-absorption modulated laser (EML) package that encloses the semiconductor laser and the SOA, the EML package including:

a first electrical contact electrically coupled to at least one of the anode electrode of the SOA or the anode electrode of the semiconductor laser;

a second electrical contact electrically coupled to at least one of the cathode electrode of the SOA or the cathode electrode of the semiconductor laser; and

an optical output port configured to provide an output amplified optical signal; and

at least one of:

a thermo-electric cooler (TEC) thermally coupled to the substrate, the TEC electrically coupled to a third electrical contact and a fourth electrical contact of the EML package;

Appln. No.: 10/644,570

**TNT-114US** 

a feedback monitor optically coupled to the semiconductor laser, the feedback monitor being electrically coupled to a fifth electrical contact and a sixth electrical contact of the EML package; or

an optical modulator optically coupled to the SOA, the optical modulator being electrically coupled to a seventh electrical contact of the EML package;

wherein;

the semiconductor laser and the SOA are configured on the substrate so that the laser is optically coupled to the SOA; and

at least one of the semiconductor laser anode electrode or semiconductor laser cathode electrode is electrically coupled to at least one of the amplifier anode electrode or amplifier cathode electrode such that the semiconductor laser and the SOA are electrically connected in series or in parallel.

- 4. (Original) The amplified laser of claim 1, wherein the cathode electrode of the semiconductor laser is electrically coupled to the anode electrode of the SOA whereby the semiconductor laser and SOA are connected in series.
- 5. (Previously Amended) The amplified laser of claim 4, further comprising an electronic component electrically coupled in parallel to at least one of the semiconductor laser or the SOA.
- 6. (Previously Amended) The amplified laser of claim 5, wherein the electronic component includes at least one of a resistor, a capacitor, an inductor, or an integrated circuit.
- 7. (Original) The amplified laser of claim 1, wherein the anode electrode of the semiconductor laser is electrically coupled to the cathode electrode of the SOA whereby the semiconductor laser and the SOA are connected in series.

04-26-06 03:18pm From-Ratner Prestia

Appln. No.: 10/644,570

**TNT-114US** 

The amplified laser of claim 7, further (Previously Amended) comprising an electronic component electrically coupled in parallel to one of the semiconductor laser or the SOA.

The amplified laser of claim 8, wherein the 9. (Previously Amended) electronic component includes at least one of a resistor, a capacitor, an inductor, or an integrated circuit.

10-22 (Canceled)